

Technical Information

FreezPoint™

Anti - Gel / Winterizing Agent lowers the pour point of distillate fuels approximately 10°F when used at a rate of 1 gallon per 2,000 gallons of diesel fuel and 20°F when used at 1 gallon per 1,000 gallons of diesel fuel.

For Diesel Fuel ONLY

Distributed By: Syntek Global Inc.
12382 South Gateway Park Place Suite B800
Draper, UT 84020
801-386-5007



FreezPoint™

Anti - Gel / Winterizing Agent

FreezPoint™ lowers the pour point of distillate fuels approximately 10°F when used at a rate of 1 gallon per 2,000 gallons of diesel fuel and 20°F when used at 1 gallon per 1,000 gallons of diesel fuel. FOR DIESEL FUEL ONLY.

Features include

- Dissolves readily in fuel even when cold
- Pours easily
- No special shipping required in drum or smaller packages
- Proven effective on biodiesel blends to B-20
- Ultra Low Sulfur Diesel Compliant

Specifications

Nominal Density	7.3 lbs./gal.
Typical Color	Clear to slightly white
Sulfur Content	<15 PPM
Nominal Flashpoint ASTM D93	145°F
Form	Liquid
Solubility in Fuel	100%
Normal Treatment Rate	1:1,000 to 1:2,000 (can be increased if needed)

Application

FreezPoint™ is formulated to be completely soluble in both petroleum and blended biodiesel fuels and is designed to be added directly to fuels at a rate of 1 gallon per 2,000 gallons of distillate fuel or more as necessary.